

Ref. 9SNUG10

Synthetic Boots

PU

Boots



S5



The +

- * Excellent grip.
- * Energy absorption in the heel area.
- * Snugfit : tighter fit around the foot, improving walking comfort.
- * Purotex upper: waterproof and breathable.

PURCHASE PACKAGING

Ref.	Size	Carton
9SNUG10037	37	6
9SNUG10038	38	6
9SNUG10041	41	6
9SNUG10042	42	6
9SNUG10043	43	5
9SNUG10046	46	5
9SNUG10047	47	5
9SNUG10048	48	5

Some sizes may only be available in certain countries

DESCRIPTION

safety boots with excellent handling properties, energy absorption in the heel area, tight fitting for a better feel, improved walking comfort. upper in waterproof but breathable purotex®. s5

SECTORS

Farming, silviculture and fishing

Extracting Oil and Gas

Heavy & process industries

Light Industries

Regional/public authorities

Infrastructure, building industry

TECHNICAL FEATURES

Color	Anthracite
Weight	1190 g
Upper	Purofort® / Purotex®
Toecap	Composite
Puncture resistant sole	Textile
Outsole	Purofort®

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)



EPI CAT. II

EN ISO 20345:2011

S5

Safety shoes

S5 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

CI

Shoe insulation against cold (30 minutes at -20°C)