

Ref. **9RUBH**

Specialties

High

High shoes



The +

- * Breathable upper and lining.
- * Heel scuff cap.
- * Padding for snug fit.
- * Rounded heel for more comfortable driving.

PURCHASE PACKAGING

Ref.	Size	Carton
9RUBH36	36	10
9RUBH37	37	10
9RUBH38	38	10
9RUBH39	39	10
9RUBH40	40	10
9RUBH41	41	10
9RUBH42	42	10

Some sizes may only be available in certain countries

See also

VARIANTS



9RUBL

DESCRIPTION

Composite toecap
Antipenetration textile Wellmax sole
External sole in Rubber
Plastic eyelets
Upper in Nubuck

SECTORS

Food-processing industry

Regional/public authorities

Construction - finishing work

Transport (excluding manufacturing) and logistics

TECHNICAL FEATURES

Color	Black	Insole	attached, textile and foam
Color 2	Grey	Main assembly	Injected
Weight	529 g	Reinforcement material	Anti-abrasion Stark [®]
Upper	Polyamide mesh / Nubuck leather	Reinforcement location	Heel
Toecap	Composite	Closing	Lacing closure
Puncture resistant sole	Textile	Lining	Breathable 3D mesh
Midsole	PU		
Outsole	Rubber nitrile		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/12/24/2980

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

HRO

Heat contact resistant outsole (60 seconds at 300°C)

EN ISO 20345:2022

Safety shoes

S3L

S3L Basic requirements : a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton + - closed heel area- antistatic properties- energy-absorbing capacity of the heel Puncture resistance:- Sole puncture resistance (1100 Newton)- Non-metallic insert, 4.5mm diameter puncture needle+ non-metallic insert type PL - resistance to penetration and water absorption of the upper- puncture resistance according to type- cleated outsole

FO

Hydrocarbons resistance