

Ref. **9SODL50**

Multipurpose

Low

Low shoes



S1P



0%
METAL

The +

- * Breathable upper and lining.
- * Footbridge supplying torsional rigidity.
- * Midsole with front protective covering.

PURCHASE PACKAGING

Ref.	Size	Carton
9SODL50038	38	6
9SODL50039	39	6
9SODL50040	40	6
9SODL50041	41	6
9SODL50042	42	6
9SODL50043	43	6
9SODL50044	44	6
9SODL50045	45	6
9SODL50046	46	6
9SODL50047	47	6

Some sizes may only be available in certain countries



DESCRIPTION

Composite toecap
Antipenetration textile sole
External sole in double density PU/PU
Upper in Suede
Non woven lining
Padded bellows
Padded collar

SECTORS

Infrastructure, building industry

Construction - finishing work

Transport (excluding manufacturing) and logistics

Services and distribution

APPLICATIONS

Luggage handler,
Delivery driver, ...

TECHNICAL FEATURES

Color	Grey	Insole	Textile and foam, removable
Color 2	Blue	Main assembly	Injected
Weight	598 g	Closing	Lacing closure
Upper	Suede leather / Mesh	Lining	Breathable 3D mesh
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/10/21/1787 EXT 01/10/21

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S1P

SRC

Safety shoes

S1P Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol