

Ref. **9TOPH**

Outdoor

High

High shoes



HRO



The +

- * Footbridge supplying torsional rigidity.
- * Padded collar and bellows tongue for snug fit.

PURCHASE PACKAGING

| Ref. | Size | Carton |
|---------|------|--------|
| 9TOPH38 | 38 | 10 |
| 9TOPH39 | 39 | 10 |
| 9TOPH40 | 40 | 10 |
| 9TOPH41 | 41 | 10 |
| 9TOPH42 | 42 | 10 |
| 9TOPH43 | 43 | 10 |
| 9TOPH44 | 44 | 10 |
| 9TOPH45 | 45 | 10 |
| 9TOPH46 | 46 | 10 |
| 9TOPH47 | 47 | 10 |

Some sizes may only be available in certain countries

See also

VARIANTS



9TOPL0

DESCRIPTION

Composite toecap
Antipenetration textile sole
External sole in double density PU/Rubber
Upper in crazy horse leather
Breathable mesh lining
Reinforcement : front in PU and back in TPU

SECTORS

Mining
Extracting Oil and Gas
Energy (production and distribution)
Infrastructure, building industry

APPLICATIONS

Builder,
Slater,
Ramp agent,
Luggage handler,
Site supervisor,
Dockers, ...

TECHNICAL FEATURES

| | | | |
|-------------------------|--------------------|---------------|-----------------------------|
| Color | Brown | Insole | Removable, textile and foam |
| Color 2 | Black | Main assembly | Injected |
| Weight | 762 g | Closing | Lacing closure |
| Upper | Full grain leather | Lining | Breathable 3D mesh |
| Toecap | Composite | | |
| Puncture resistant sole | Textile | | |
| Midsole | PU | | |
| Outsole | Rubber nitrile | | |

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC F100341289**

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

HRO

Heat contact resistant outsole (60 seconds at 300°C)