

Ref. **9SAND20**

Outdoor

High

High shoes



The +

- *EVA/nitrile rubber outsole: flexible and resistant for long-lasting wear.
- *Oxford fabric cut-out at the ankle: optimized flexibility.
- *Anti-abrasion protection at the back: safety.

PURCHASE PACKAGING

Ref.	Size	Carton
9SAND20036	36	6
9SAND20037	37	6
9SAND20038	38	6
9SAND20039	39	6
9SAND20040	40	6
9SAND20041	41	6
9SAND20042	42	6
9SAND20043	43	6
9SAND20044	44	6
9SAND20045	45	6
9SAND20046	46	6
9SAND20047	47	6

Some sizes may only be available in certain countries

DESCRIPTION

The SAND model combines comfort and solidity. Recommended for all outdoor work, it is equipped with a waterproof upper. Its EVA midsole and nitrile rubber outsole provide stability and support for the user. This model is equipped with a composite / textile protection.

SECTORS

Mechanicals constructions

Regional/public authorities

Maintenance

Infrastructure, building industry

Construction - finishing work

Transport (excluding manufacturing) and logistics

TECHNICAL FEATURES

Color	Beige	Lining	Breathable 3D mesh
Weight	572 g		
Upper	Nubuck leather		
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	EVA		
Outsole	Rubber nitrile		
Closing	Lacing closure		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/06/22/1092

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

HRO

Heat contact resistant outsole (60 seconds at 300°C)

COVERPERF - Damping



Shoes tested in a certified laboratory (CTC) offering excellent damping. Over 25% of the impact force is absorbed by the sole.