

Ref. **9SCHH10**

Multipurpose

High

High shoes



The +

- * Sport design
- * Metal free
- * Reflective trim
- * Defined and raised heel

PURCHASE PACKAGING

Ref.	Size	Carton
9SCHH10038	38	6
9SCHH10039	39	6
9SCHH10040	40	6
9SCHH10041	41	6
9SCHH10042	42	6
9SCHH10043	43	6
9SCHH10044	44	6
9SCHH10045	45	6
9SCHH10046	46	6
9SCHH10047	47	6

Some sizes may only be available in certain countries

See also

VARIANTS



9SCH100

DESCRIPTION

SCHORL is a high safety shoe inspired by the trail universe. Its upper made of Oxford polyester provides breathability and durability. The front, sides and back reinforcements in KPU increase long lastingness and is suitable to users working squatting or kneeling. Reflective stripes improve safety of people working at night. Metal free, this shoe features a composite toe-cap and a textile anti-penetration sole that bring better flexibility and better thermal insulation than steel shoes. The nitrile rubber clitted outsole and polyurethane midsole combine the advantages of both materials: comfort and resistance. SCHORL suits the requirements of standard indoor and outdoor uses.

SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

TECHNICAL FEATURES

Color	Black	Closing	Lacing closure
Weight	702 g	Lining	Breathable 3D mesh
Upper	Mesh		
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	Rubber nitrile		
Insole	Removable, perforated EVA		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/12/24/3039 EXT 01/12/24

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2022

S3S

Safety shoes

S3S Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton+ closed heel area- antistatic properties- energy-absorbing capacity of the heel Puncture resistance:- Resistance of the sole to puncture (min.1100 N and individual value \geq 950 N) - Non-metallic insert, 3.0mm diameter puncture needle+ non-metallic insert type PS - resistance to penetration and water absorption of the upper- puncture resistance according to type- cleated outsole

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance