

Ref. **9SIL150**

Multipurpose

Low

Low shoes



S3

SR

FO



The +

- *Breathable and water repellent upper.
- *Heel and toe scuff cap.
- *Reflective stripe with multiple faces.

PURCHASE PACKAGING

Ref.	Size	Carton
9SIL150037	37	6
9SIL150038	38	6
9SIL150039	39	6
9SIL150040	40	6
9SIL150041	41	6
9SIL150042	42	6
9SIL150043	43	6
9SIL150044	44	6
9SIL150045	45	6
9SIL150046	46	6
9SIL150047	47	6

Some sizes may only be available in certain countries

See also

VARIANTS



9SIH150

DESCRIPTION

SILVER is a waterproof shoe, in suede and nylon. The breathability of the materials that make up this model make it a safety shoe with comfortable use and long-lasting performance. Equipped with a steel toe cap and midsole, it also features a dual density PU outsole. The shoe is designed to resist slipping on steel and ceramic floors.

SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

TECHNICAL FEATURES

Color	Anthracite	Main assembly	Injected
Weight	653 g	Closing	Lacing closure
Upper	Suede leather / Polyamide mesh	Lining	Moisture wicking non-woven membrane
Toecap	Steel		
Puncture resistant sole	Steel		
Midsole	PU		
Outsole	PU		
Insole	Textile and foam, removable		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/08/23/1342

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2022

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance