

Ref. **9STH370**

Outdoor

High

High shoes



S3



The +

- *Shaped cleats: adherence and gripping on rough floors.
- *Grooves for liquid and mud dispersement.
- *Raised heel 1 cm and lateral edges: reinforced grip on ladders.
- *TPU outsole: strength and durability.
- *Front and back reinforcements.

PURCHASE PACKAGING

Ref.	Size	Carton
9STH370035	35	6
9STH370036	36	6
9STH370037	37	6
9STH370038	38	6
9STH370039	39	6
9STH370040	40	6
9STH370041	41	6
9STH370042	42	6
9STH370043	43	6
9STH370044	44	6
9STH370045	45	6
9STH370046	46	6
9STH370047	47	6
9STH370048	48	6

Some sizes may only be available in certain countries

See also

VARIANTS



9STH370

DESCRIPTION

STONE is a formidable efficiency safety shoe. Specially designed for construction industry, STONE benefits from a PU / TPU sole resistant to abrasion, oils and hydrocarbons and equipped with prominent grips. Its pull-up leather upper has good waterproofing. STONE features a toe-cap and an anti-penetration plate made of composite for optimal protection. Its removable insole, made of textile and EVA with wide perforations, offers good evacuation of perspiration.

SECTORS

Mining

Extracting Oil and Gas

Energy (production and distribution)

Infrastructure, building industry

TECHNICAL FEATURES

Color	Brown	Main assembly	Injected
Weight	720 g	Closing	Lacing closure
Upper	Pull-up leather	Lining	Breathable 3D mesh
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	TPU		
Insole	Removable, perforated EVA		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/02/21/0281

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol