

Ref. **9TEKL50**

Indoor and dry environments

Low

High shoes



S1P



HRO

0%
METAL

The +

- * Breathable upper and lining.
- * Padded collar and bellows tongue: snug fit.
- * Reflective strip: visibility.

PURCHASE PACKAGING

Ref.	Size	Carton
9TEKL50039	39	6
9TEKL50040	40	6
9TEKL50041	41	6
9TEKL50042	42	6
9TEKL50043	43	6
9TEKL50044	44	6
9TEKL50045	45	6
9TEKL50046	46	6

Some sizes may only be available in certain countries

DESCRIPTION

Composite toecap
Antipenetration textile Wellmax sole
External sole in Rubber
Textile tightening loops, High shoes plastic hooks
Padded collar
Upper in PU Nubuck and mesh
Breathable mesh lining
Padded tongue

SECTORS

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

APPLICATIONS

Painter,
Electrician,
Storekeeper, ...

TECHNICAL FEATURES

Color	Black	Main assembly	Cemented
Color 2	Grey	Closing	Lacing closure
Weight	580 g	Lining	Breathable 3D mesh
Upper	Polyamide mesh / Polyurethane		
Toecap	Composite		
Puncture resistant sole	Textile		
Outsole	Rubber nitrile		
Insole	Removable, textile and foam		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate ITASLNB21026456

Delivered by INTERTEK Italia S.p.A. (2575) Via Guido Miglioli 2/A 20063 Cernusco sul Naviglio - Milano (MI) Italy



EPI CAT. II

EN ISO 20345:2011

S1P

Safety shoes

S1P Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure

SRA

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

HRO

Heat contact resistant outsole (60 seconds at 300°C)