

Ref. **9STH370**

Outdoor

High

High shoes



**S3S**

**SR**

**FO**



The +

- \*Shaped cleats: adherence and gripping on rough floors.
- \*Grooves for liquid and mud dispersement.
- \*Raised heel 1 cm and lateral edges: reinforced grip on ladders.
- \*TPU outsole: strength and durability.
- \*Front and back reinforcements.

### PURCHASE PACKAGING

Ref.	Size	Carton
9STH370035	35	6
9STH370036	36	6
9STH370037	37	6
9STH370038	38	6
9STH370039	39	6
9STH370040	40	6
9STH370041	41	6
9STH370042	42	6
9STH370043	43	6
9STH370044	44	6
9STH370045	45	6
9STH370046	46	6
9STH370047	47	6
9STH370048	48	6

*Some sizes may only be available in certain countries*

See also

### VARIANTS



9STH370

### DESCRIPTION

STONE is a formidable efficiency safety shoe. Specially designed for construction industry, STONE benefits from a PU / TPU sole resistant to abrasion, oils and hydrocarbons and equipped with prominent grips. Its pull-up leather upper has good waterproofing. STONE features a toe-cap and an anti-penetration plate made of composite for optimal protection. Its removable insole, made of textile and EVA with wide perforations, offers good evacuation of perspiration.

### SECTORS

Mining

Extracting Oil and Gas

Energy (production and distribution)

Infrastructure, building industry

## TECHNICAL FEATURES

Color	Brown	Main assembly	Injected
Weight	720 g	Closing	Lacing closure
Upper	Pull-up leather	Lining	Breathable 3D mesh
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	TPU		
Insole	Removable, perforated EVA		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/02/21/0281

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2022

S3S

Safety shoes

**S3S** Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton+ closed heel area- antistatic properties- energy-absorbing capacity of the heel Puncture resistance:- Resistance of the sole to puncture (min.1100 N and individual value  $\geq$  950 N) - Non-metallic insert, 3.0mm diameter puncture needle+ non-metallic insert type PS - resistance to penetration and water absorption of the upper- puncture resistance according to type- cleated outsole

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance