

Ref. **9TEEH**

Specialties

High

High shoes



The +

- \* Anti-torsion support for the arch.
- \* Padded collar and gusseted Tongue for better support.
- \* Detached Heel.
- \* Outsole resistant to electrical hazards (ASTM F-2413-17 EH).

### PURCHASE PACKAGING

Ref.	Size	Carton
9TEEH37	37	10
9TEEH38	38	10
9TEEH39	39	10
9TEEH40	40	10
9TEEH41	41	10
9TEEH42	42	10
9TEEH43	43	10
9TEEH44	44	10
9TEEH45	45	10
9TEEH46	46	10
9TEEH47	47	10
9TEEH48	48	10

*Some sizes may only be available in certain countries*

See also

VARIANTS



9FEEH

### DESCRIPTION

The TOPAZ is a high safety shoe with a full grain leather upper and breathable 3D mesh lining. It has front and back reinforcements in order to ensure a better protection and a longer lifetime. It has an electrical hazards resistant outsole (ASTM F-2413-17 EH).

This metalfree safety shoe has a composite toecap and an anti-perforation textile sole which guarantees lightness.

### SECTORS

- Mining
- Extracting Oil and Gas
- Energy (production and distribution)
- Infrastructure, building industry
- Construction - finishing work

### APPLICATIONS

- Electrician
- Mining and quarrying
- Oil and gas industry

## TECHNICAL FEATURES

Color	Brown	Insole	Removable, textile and foam
Color 2	Black	Main assembly	Injected
Weight	762 g	Closing	Lacing closure
Upper	Full grain leather	Lining	Breathable 3D mesh
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	Rubber nitrile		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **CE-PC-240719-328-01-9A**

Delivered by CCQS UK LTD (1105) Level 2 5 Harbour Exchange Square London- E14 9GE United Kingdom



EPI CAT. II

HRO

Heat contact resistant outsole (60 seconds at 300°C)

EN ISO 20345:2022

Safety shoes

SB

SB Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton including ceramic/NaLS slip resistance

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance