

Ref. **9XCRH70**

Outdoor

High

High shoes



The +

PERFORMANCE : high cleats designed to promote grip and stability
COIMFORT : insert for good cushioning and joint vibration prevention//
 carbon toe cap = robustness
DURABILITY : front (SC marking) and rear reinforcements for greater resistance in the event of rubbing or contact with an aggressive surface//
 rigid laces and riveted eyelets for greater durability

DESCRIPTION

X-CLAW ROBUST is a full-grain leather safety shoe. Its reinforcements at the front (SC marking) and back of the foot provide protection and durability. X-CLAW ROBUST has been designed for use in damp environments.

X-CLAW is above all a unique sole designed to offer grip, stability and durability:

- Its large, inverted studs provide grip on all loose and uneven surfaces.
- Its rear platform and transverse studs (LG marking) ensure safety and prevent the risk of falling, even on ladders.
- Its wear indicator and the quality of its PU also contribute to its durability.

Finally, the insert integrated into the sole provides good cushioning and prevents vibrations from affecting the joints.

As for the upper, its carbon toe cap provides impact resistance, lightness, thinness and does not conduct heat.

SECTORS

Regional/public authorities
 Infrastructure, building industry
 Construction - finishing work

APPLICATIONS

Landscaper, Public Works, Builder, Mason, Machine Operator, Surveyor, Earthworker, ... (non-exhaustive list)

PURCHASE PACKAGING

Ref.	Size	Carton
9XCRH70035	35	6
9XCRH70036	36	6
9XCRH70037	37	6
9XCRH70038	38	6
9XCRH70039	39	6
9XCRH70040	40	6
9XCRH70041	41	6
9XCRH70042	42	6
9XCRH70043	43	4
9XCRH70044	44	4
9XCRH70045	45	4
9XCRH70046	46	4
9XCRH70047	47	4
9XCRH70048	48	4

Some sizes may only be available in certain countries

See also

VARIANTS

TECHNICAL FEATURES

Color	Brown	Insole	Removable, textile and foam
Color 2	Black	Main assembly	Injected
Weight	748 g	Front bumper	
Upper	Full grain leather	Reinforce-ment material	TPU
Toecap	Carbon	Closing	Lacing closure
Puncture resistant sole	Textile	Lining	Breathable 3D mesh
Midsole	PU	Defined heel	
Outsole	PU		

INSTRUCTION FOR USE AND STORAGE

Instructi-ons for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructi-ons

Place the shoes, when not in use, in a dry, clean and airy place. The tim einfluences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructi-ons

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **CE-PC-240530-249-02-9A**

Delivered by CCQS Certification Services Limited (2384) Block 1 Blanchardstown Corporate Park- Ballycoolin Road- Blanchardstown- Dublin 15 D15 AKK1 Dublin Ireland



EPI CAT. II

HI

Sole insulation against heat (30 minutes at 150°C)

CI

Shoe insulation against cold (30 minutes at -20°C)

COVERPERF - Damping



Shoes tested in a certified laboratory (CTC) offering excellent damping. Over 25% of the impact force is absorbed by the sole.

EN ISO 20345:2022

S3S

Safety shoes

S3S Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton+ closed heel area- antistatic properties- energy-absorbing capacity of the heel Puncture resistance:- Resistance of the sole to puncture (min.1100 N and individual value ≥ 950 N) - Non-metallic insert, 3.0mm diameter puncture needle+ non-metallic insert type PS - resistance to penetration and water absorption of the upper- puncture resistance according to type- cleated outsole

SR

Resistance to slippage (ceramic floor + oil)

LG

Grip System - Unhooked heel

AN

Protection of the malleoli (ankles)

MAJ 23/10/2024 SC

Abrasion resistance of the toe-caps