

Ref. **9TOPH**

Outdoor

High

High shoes



The +

- * Arch of the foot anti-torsion reinforcement.
- * Padded cuff and bellows Tongue for better support.
- * Detached Heel.

PURCHASE PACKAGING

Ref.	Size	Carton
9TOPH36	36	10
9TOPH37	37	10
9TOPH38	38	10
9TOPH39	39	10
9TOPH40	40	10
9TOPH41	41	10
9TOPH42	42	10
9TOPH43	43	10
9TOPH44	44	10
9TOPH45	45	10
9TOPH46	46	10
9TOPH47	47	10

Some sizes may only be available in certain countries

See also

VARIANTS



9TOPLO

DESCRIPTION

Composite toecap
 Antipenetration textile sole
 External sole in double density PU/Rubber
 Upper in crazy horse leather
 Breathable mesh lining
 Reinforcement : front in PU and back in TPU

SECTORS

- Mining
- Extracting Oil and Gas
- Energy (production and distribution)
- Infrastructure, building industry

APPLICATIONS

Builder,
 Slater,
 Ramp agent,
 Luggage handler,
 Site supervisor,
 Docker, ...

TECHNICAL FEATURES

Color	Brown	Insole	Removable, textile and foam
Color 2	Black	Main assembly	Injected
Weight	762 g	Closing	Lacing closure
Upper	Full grain leather	Lining	Breathable 3D mesh
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	Rubber nitrile		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 2777/24395-01/E00-00

Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park- Clonee- Dublin 15 Dublin Ireland



EPI CAT. II

HRO

Heat contact resistant outsole (60 seconds at 300°C)

EN ISO 20345:2022

Safety shoes

S3S

S3S Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton+ closed heel area- antistatic properties- energy-absorbing capacity of the heel Puncture resistance:- Resistance of the sole to puncture (min.1100 N and individual value ≥ 950 N) - Non-metallic insert, 3.0mm diameter puncture needle+ non-metallic insert type PS - resistance to penetration and water absorption of the upper- puncture resistance according to type- cleated outsole

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance