

Ref. **9VOSH**

Specialties

High

High shoes



S3



HRO

The +

- * Heat and moisture resistant outsole.
- * Defined heel for better safety especially on ladders.

PURCHASE PACKAGING

Ref.	Size	Carton
9VOSH38	38	10
9VOSH39	39	10
9VOSH40	40	10
9VOSH41	41	10
9VOSH42	42	10
9VOSH43	43	10
9VOSH44	44	10
9VOSH45	45	10
9VOSH46	46	10
9VOSH47	47	10

Some sizes may only be available in certain countries

DESCRIPTION

VOLCANITE is a full grain leather safety shoe with a padded ankle and tongue.

Its nitrile rubber outsole is non-slip on ceramic floors and resistant to very high temperatures (up to 300°C on contact for one minute).

This model guarantees foot protection thanks to a protective toe cap and an anti-puncture steel midsole.

SECTORS

Infrastructure, building industry

Construction - finishing work

Transport (excluding manufacturing) and logistics

Services and distribution

APPLICATIONS

Luggage handler,
Delivery driver, ...

TECHNICAL FEATURES

Color	Black	Lining	Moisture wicking non-woven membrane
Weight	846 g	Defined heel	
Upper	Full grain leather		
Toecap	Steel		
Puncture resistant sole	Steel		
Outsole	Rubber nitrile		
Insole	Attached, textile and foam		
Closing	Lacing closure		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate ITALSLNB22020222

Delivered by INTERTEK Italia S.p.A. (2575) Via Guido Miglioli 2/A 20063 Cernusco sul Naviglio - Milano (MI) Italy



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRA

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

HRO

Heat contact resistant outsole (60 seconds at 300°C)