coverguard

TECHNICAL DATASHEET

MO23105

Ref. MO23105

Non Reusable







FFP1 NR D



The +

Electrostatic filter media Sliding elastic band : better adjustment, without latex Exhalation valve : reduction of breathing resistance and avoid fog inside the mask

Seal outside contours, reduces the risk of irritation

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
23105	-		12

SALES PACKAGING



Multiple

with exhalation valve, latex free synthetic rubber, adjustable nose clip

DESCRIPTION

SECTORS

Farming, silviculture and fishing

- Mining
- Light Industries

Infrastructure, building industry

Construction - finishing work

DIY

APPLICATIONS

FFP1 disposable foldable half mask made of non-woven polypropylene

For occasional use in a very dusty environment. Protections against non-toxic solid and liquid aerosols, such as calcium carbonate, kaolin, cement, cellulose, sulfur, cotton, flour, coal, ferrous metals, vegetable oils and tender woods. Textile industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork (strong woods excepted).

See also



coverguard

MO23105

TECHNICAL FEATURES

Shape	Flat foldable mask	Main risk
Weight	17g	
Specifications	FFP1 NR D	Color
Harness	Synthetic elastic rubber (latex free)	Features
features		

Respiratory protection from aerosols and non toxic dust White FFP1

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate CE 697918

Delivered by BSI Group The Netherlands B.V (2797) Say Building- John M. Keynesplein 9-1066 EP Amsterdam Netherlands

CE

EPI CAT. III

EN149:2001 + A1:2009 FFP1 Particle filtering half masks