# coverguard®

## **TECHNICAL DATASHEET**

# MO23246

Ref. MO23246

#### Non Reusable



FFP2 NR D VO GA



## The +

bad odours and acid gases
Exhalation valve: reduction of
breathing resistance and avoid fog
inside the mask
Adjustable alu nose clip and
comfortale nasal cushions with
polyethylene foam
Latex free elastic band

Electrostatic filter media which filters

#### **PURCHASE PACKAGING**

Ref. Size Inner Carton 23246 - 12

#### SALES PACKAGING

>1

Multiple

## DESCRIPTION

FFP2 half-mask made of non-woven polypropylene with exhalation valve and active carbon, latex free synthetic rubber, aluminium adjustable nose clip, PU foam nose pad

#### **SECTORS**

Heavy & process industries

Chemical & pharmaceutical industries

Light Industries

Infrastructure, building industry

Construction - finishing work

DIY

#### **APPLICATIONS**

For occasional use in a very dusty environment. Protections against non-toxic solid and liquid aerosols, such as calcium carbonate, kaolin, cement, cellulose, sulfur, cotton, flour, coal, ferrous metals, vegetable oils and tender woods.

Textile industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork (strong woods excepted).

### **TECHNICAL FEATURES**

Shape Hull mask Weight 18 g

Specifications FFP2 NR D VO GA

Harness Synthetic elastic rubber (latex free)

features

Main risk Respiratory protection from aerosols and

low toxic dust, organic vapours, gas and

acids

Color Blue Color 2 White

Features Non woven polypropylene and polyester

with valve

Aluminum nose clip

Latex free synthetic rubber bands

PU foam nose pad

## STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate CE 697918

Delivered by BSI Group The Netherlands B.V (2797) Say Building- John M. Keynesplein 9-1066 EP Amsterdam Netherlands

( (

EPI CAT. III

EN149:2001 + A1:2009 FFP2 NR D Particle filtering half masks

MAJ 27/09/2023