

Ref. **MO23316**

Non Reusable

FFP3 NR D



The +

Specific design of the exhalation valve: high reduction of the breathing resistance
Preformed design: fits with glasses or goggles to avoid the risk of condensation
The ergonomic form offers an optimal adjustment to the face without nose clip.

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
23316	-		12

SALES PACKAGING



Multiple

DESCRIPTION

FFP3 disposable preformed half-mask made of nonwoven polypropylene, external layer in polyester with exhalation valve, PU foam total nose seal, latex free synthetic rubber

SECTORS

Mining
Heavy & process industries
Chemical & pharmaceutical industries
Light Industries
Regional/public authorities
Infrastructure, building industry
Construction - finishing work

APPLICATIONS

For occasional use in a very dusty environment. Protections against non-toxic solid and liquid aerosols, such as calcium carbonate, kaolin, cement, cellulose, sulfur, cotton, flour, coal, ferrous metals, vegetable oils and tender woods.
Textile industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork (strong woods excepted).

TECHNICAL FEATURES

Shape	Ergonomic mask	Main risk	Respiratory protection from toxic aerosols and dusts
Weight	17g	Color	White
Specifications	FFP3 NR D	Features	Polyester / polypropylene SMS
Harness features	Synthetic elastic rubber (latex free)		

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **CE 697918**

Delivered by BSI Group The Netherlands B.V (2797) Say Building- John M. Keynesplein 9- 1066 EP Amsterdam Netherlands



EPI CAT. III

EN149:2001 + A1:2009
FFP3 NR D

Particle filtering half masks