

TECHNICAL DATASHEET

EUROSTRONG 150

Ref.

MO150

General & Heavy Duty Works





Textile/Leather

The +

Vein protection patch

PURCHASE PACKAGING

 Ref.
 Size
 Inner
 Carton

 150
 10
 12
 120

SALES PACKAGING

>1

Multiple

See also

VARIANTS



MO140

DESCRIPTION

Docker glove in grey split cowhide leather, Cotton lined palm, back and cuff in white fabric, 7,5cm safety cuff

SECTORS

Mining

Infrastructure, building industry

Construction - finishing work

Transport (excluding manufacturing) and logistics

APPLICATIONS

General and heavy handling in dry and low-soiling environments, wood and carpentry, transport and warehousing activities.

TECHNICAL FEATURES

Color Ecru Shape Glove

Gloves environme-nt Dry environment Glove type Cut and sewn

Support material Split leather cowhide

Glove construct-ion
Palm material
Type of palm leather
Finition palm leather
Back material
Back material type
Cotton
Cotton fabric

Reinforce-d part place Back

Reinforce-d part material Lining material Type Of Cuff

Glove thickness - mm

Leather/Split leather Cotton fabric

Safety cuff / Artery protector /

Straight cut

1.0 - 1.2mm

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 2777/12287-02/E00-00

Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park- Clonee- Dublin 15 Dublin Ireland

 ϵ

EPI CAT. II

EN ISO 21420:2020

Protective gloves – General requirements and test methods

Protection from mechanical risks

