

Ref. 1PULD40

Handling and Precision Works

Dry Environment



The +

COVERPERF DURABILITY: Washability - Performance guaranteed up to 5 cycles at 40°C // Touchscreen // Extended service life (Abrasion 4) // Silicone-free (VDMA test) : ideal for painting metal and slick surfaces

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
1PULD40006	6	10	100
1PULD40007	7	10	100
1PULD40008	8	10	100
1PULD40009	9	10	100
1PULD40010	10	10	100
1PULD40011	11	10	100
1PULD40012	12	10	100

SALES PACKAGING



Hangable individual polybag

See also

VARIANTS



1PULD50

DESCRIPTION

EUROLITE P400. White fine polyamide seamless support, 13 gauge, close fitting. White polyurethane palm coating; Knitted wrist; Touchscreen. DMF level < 10ppm. Silicon free. VDMA TEST RESULTS: solvent-based paint the gloves are Labs-conform on all classes (A1, A2 and A3) -> VDMA24364-A1/A2/A3-L // water-based paint the gloves are conform on all classes (A1, A2) --> VDMA24364-A1/A2-W

SECTORS

- Mechanicals constructions
- Light Industries
- Food-processing industry
- Maintenance
- Services and distribution

APPLICATIONS

Fine handling and precise assembly of parts, meticulous assembly work, sorting of small parts, small screws and bolts, assembly of electronic components. Especially recommended for painting, automotive industries, car bodywork, epoxy, solvents... Food contact compliant

TECHNICAL FEATURES



Gauge 13

Color	White
Color 2	White
Shape	Glove
Gloves environment	Dry environment
Glove type	Seamless knitting
Support material	Polyamide
Coating level	Palm
Material of coating	PU
Coating finition	Smooth
Type Of Cuff	Elastic wrist

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/162/09/21/1617

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 21420:2020

Protective gloves – General requirements and test methods

EN388:2016
+ A1:2018

Protection from mechanical risks



4.1.2.1.X.

Food contact



The overall and specific migration of substances subject to restriction has been tested according to EU Regulation 10/2011 and does not exceed any legal migration levels. Supporting documents are available upon request.
The product has been tested against simulant food types A, B and D2 of Regulation No.10/2011 for Plastic Materials and Articles in contact with all food types, aqueous and fatty foods 0,5 hour at 40°C for repeat use.

COVERPERF -
Durability/Washable

