coverguard®

TECHNICAL DATASHEET

EUROSTRONG 155

Ref.

MO155

General & Heavy Duty Works



Textile/Leather





The +

Superior quality
Vein protection patch
Safety cuff
Extended service life

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
148	8	10	60
155	10	10	60
155_11	11	10	60
155L	12	10	60

SALES PACKAGING

>1

Multiple

See also

DESCRIPTION

Docker glove in grey split cowhide leather, Cotton lined palm, back and cuff in strong red fabric, 8cm safety cuff

SECTORS

Mining

Infrastructure, building industry

Construction - finishing work

Transport (excluding manufacturing) and logistics

APPLICATIONS

General and heavy material handling, activity of warehouseman (storage, handling of boxes and crates), heavy gardening work, wood trades (logging, carpentry), construction and public works (masonry).

VARIANTS



MO152

TECHNICAL FEATURES

ColorRedColor 2GreyShapeGlove

Gloves environme-nt
Glove type
Cut and sewn
Support material
Split leather cowhide, cotton

fabric

Glove construct-ion Docker
Palm material Leather
Type of palm leather Cowhide
Finition palm leather Split leather
Back material Cotton

Back material type Reinforce-d part place Reinforce-d part material Lining material Type Of Cuff Glove thickness - mm Cotton fabric Back

Leather/Split leather Brushed cotton Safety cuff / Straight cut

1.0 - 1.2mm

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/162/09/24/2077

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France

 ϵ

EPI CAT. II

EN ISO 21420:2020

Protective gloves – General requirements and test methods

EN388:2016 + A1:2018

 $\frac{1}{144X}$

Protection from mechanical risks