

Ref. MO23238

Non Reusable

FFP2 NR D VO

D



### The +

- Electrostatic filter media which filters bad odours
- Exhalation valve: reduction of breathing resistance and avoid fog inside the mask
- Adjustable alu nose clip and comfortable nasal cushions with polyethylene foam
- Latex free elastic bands

### PURCHASE PACKAGING

Ref.	Size	Inner	Carton
23238	-		12

### SALES PACKAGING

>1

Multiple

See also

### VARIANTS



MO23236



MO23246

### DESCRIPTION

FFP2 half-mask made of non-woven polypropylene with exhalation valve and active carbon, latex free synthetic rubber, aluminum adjustable nose clip, PU foam nose pad

### SECTORS

- Heavy & process industries
- Chemical & pharmaceutical industries
- Light Industries
- Infrastructure, building industry
- Construction - finishing work
- DIY

### APPLICATIONS

For occasional use in a very dusty environment. Protections against non-toxic solid and liquid aerosols, such as calcium carbonate, kaolin, cement, cellulose, sulfur, cotton, flour, coal, ferrous metals, vegetable oils and tender woods. Textile industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork (strong woods excepted).

## TECHNICAL FEATURES

Shape	Hull mask	Main risk	Respiratory protection from aerosols and low toxic dust, organic vapours, gas and acids
Weight	17g	Features	FFP2 Polyester / polypropylène SMS
Specifications	FFP2 NR D VO		
Harness features	Synthetic elastic rubber (latex free)		

## STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate 697918

Delivered by BSI Assurance UK Ltd (0086) Kitemark Court Davy Avenue Knowlhill Milton Keynes MK5 8PP United Kingdom



EPI CAT. III

EN149:2001 + A1:2009  
FFP2 NR D

Particle filtering half masks