

Ref. 1PULD50

Handling and Precision Works

Dry Environment



The +

COVERPERF DURABILITY: Washability - Performance guaranteed up to 5 cycles at 40°C
 Touchscreen
 Extended service life (Abrasion 4)
 Close fitting
 Silicone-free according to VDMA test

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
1PULD50006	6	10	100
1PULD50007	7	10	100
1PULD50008	8	10	100
1PULD50009	9	10	100
1PULD50010	10	10	100
1PULD50011	11	10	100
1PULD50012	12	10	100

SALES PACKAGING

Hangable individual polybag

See also

VARIANTS



1PULD40

DESCRIPTION

EUROLITE P500. Grey fine polyamide seamless support, 13 gauge, close fitting. White polyurethane palm coating; Knitted wrist; Touchscreen. DMF level < 30ppm. Silicon free. VDMA TEST RESULTS: solvent-based paint the gloves are Labs-conform on all classes (A1, A2 and A3) -> VDMA24364-A1/A2/A3-L // water-based paint the gloves are conform on all classes (A1, A2 and A3) --> VDMA24364-A1/A2/A3-W

SECTORS

Mechanicals constructions

Light Industries

Maintenance

Services and distribution

APPLICATIONS

Fine handling and precise assembly of parts, meticulous assembly work, sorting of small parts, small screws and bolts, assembly of electronic components.

Especially recommended for painting, automotive industries, car bodywork, epoxy, solvents...

TECHNICAL FEATURES



Gauge 13

Color	Grey
Color 2	Grey
Shape	Glove
Gloves environment	Dry environment
Glove type	Seamless knitting
Support material	Polyamide
Coating level	Palm
Material of coating	PU
Coating finition	Smooth
Type Of Cuff	Elastic wrist

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/162/07/22/1297

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 21420:2020

EN ISO 21420:2020

EN388:2016

+ A1:2018



4.1.2.1.X.

COVERPERF -
Durability/Washable



Protective gloves – General requirements and test methods

Protection from mechanical risks