

Ref. 1WEL10

Specialties

Welding



The +

Comfort, flexibility, dexterity,
Elastic band on back of hand for better fitting,
Extended service life (para-aramide seams)

PURCHASE PACKAGING

| Ref. | Size | Inner | Carton |
|------------|------|-------|--------|
| 1WEL100008 | 8 | 10 | 60 |
| 1WEL100009 | 9 | 10 | 60 |
| 1WEL100010 | 10 | 10 | 60 |
| 1WEL100011 | 11 | 10 | 60 |

SALES PACKAGING



Multiple

DESCRIPTION

Superior full grain goat leather, para-aramide stitch, wing thumb, elastic band on back of hand, safety cuff in orange split leather, length 15cm.

SECTORS

- Mechanicals constructions
- Energy (production and distribution)
- Maintenance
- Infrastructure, building industry
- Transport (excluding manufacturing) and logistics

APPLICATIONS

Protection against contact heat up to 100°C for 15 seconds; Particularly recommended for precise welding, TIG welding; Plasma cutting, gouging, flame cutting work...

TECHNICAL FEATURES

| | |
|----------------------|---|
| Color | Grey |
| Color 2 | Orange |
| Shape | Glove |
| Gloves environment | Moderate heat |
| Glove type | Cut and sewn |
| Support material | Superior full grain goat, cuff in split cowhide |
| Glove construction | Welding |
| Seams material | para-aramid |
| Type Of Cuff | Safety cuff / Straight cut |
| Glove thickness - mm | 0.7 - 0.8mm / 1.0 - 1.3mm |
| Cuff length - mm | 150 |

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/162/04/21/0667

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN420:2003 + A1:2009

General requirements for protective gloves

EN388:2016
+ A1:2018

Protection from mechanical risks



2.1.1.1.X

EN407:2004

Protection from heat and fire



4.1.2.X.4X

EN12477:2001 + A1:2005
TYPE B

Protective gloves for welders