

Ref. MO23206

Non Reusable

FFP2 NR D

D

The +



Electrostatic filter media
Exhalation valve: reduction of breathing resistance and avoid fog inside the mask
Adjustable alu nose clip and comfortable nasal cushions with polyethylene foam
Latex free elastic band

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
23206	-		12

SALES PACKAGING

>1

Multiple

DESCRIPTION

FFP2 disposable half-mask with shell and valve made of nonwoven polypropylene with valve, latex free synthetic rubber, aluminium adjustable nose clip, PU foam nose pad

SECTORS

- Heavy & process industries
- Chemical & pharmaceutical industries
- Infrastructure, building industry
- Construction - finishing work
- DIY

APPLICATIONS

For occasional use in a very dusty environment. Protections against non-toxic solid and liquid aerosols, such as calcium carbonate, kaolin, cement, cellulose, sulfur, cotton, flour, coal, ferrous metals, vegetable oils and tender woods. Textile industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork (strong woods excepted).

TECHNICAL FEATURES

Shape	Hull mask	Main risk	Respiratory protection from aerosols and low toxic dust
Weight	12g	Color	White
Specifications	FFP2 NR D	Features	FFP2
Harness features	Synthetic elastic rubber (latex free)		Polyester / polypropylene SMS

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate CE 697918

Delivered by BSI Group The Netherlands B.V (2797) Say Building- John M. Keynesplein 9- 1066 EP Amsterdam Netherlands



EPI CAT. III

EN149:2001 + A1:2009
FFP2 NR D

Particle filtering half masks