

Ref. MO23306

Non Reusable

FFP3 NR D



D

The +

Specific design: large surface of the filtering material and reduced breathing resistance
 Exhalation valve: reduction of breathing resistance and avoid fog inside the mask
 Complete face seal for a better heat and an optimal comfort



PURCHASE PACKAGING

Ref.	Size	Inner	Carton
23306	-		12

SALES PACKAGING

>1

Multiple

DESCRIPTION

FFP3 disposable half-mask made of polypropylene with shell and exhalation valve, aluminium nose clip, fabric and rubber elastic strap, PU foam total nose seal

SECTORS

- Mining
- Heavy & process industries
- Chemical & pharmaceutical industries
- Light Industries
- Regional/public authorities
- Infrastructure, building industry
- Construction - finishing work

APPLICATIONS

For occasional use in a very dusty environment. Protections against non-toxic solid and liquid aerosols, such as calcium carbonate, kaolin, cement, cellulose, sulfur, cotton, flour, coal, ferrous metals, vegetable oils and tender woods.
 Textile industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork (strong woods excepted).

TECHNICAL FEATURES

Shape	Hull mask	Main risk	Respiratory protection from toxic aerosols and dusts
Weight	18g	Features	polyester / polypropylene SMS
Specifications	FFP3 NR D		
Harness features	Wide elastic straps made of fabric		

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate CE 697918

Delivered by BSI Group The Netherlands B.V (2797) Say Building- John M. Keynesplein 9- 1066 EP Amsterdam Netherlands



EPI CAT. III

EN149:2001 + A1:2009
FFP3 NR D

Particle filtering half masks