

Ref. MO2524

Specialties

Welding



The +

Comfort
Flexibility
Split leather back : better sparks protection

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
2524	10	12	60

SALES PACKAGING

>1

Multiple

DESCRIPTION

Full grain cowhide leather in palm, back in split cowhide leather,
Wing thumb
Safety cuff in split leather, length 15cm

SECTORS

Mechanicals constructions
Energy (production and distribution)
Maintenance
Infrastructure, building industry

APPLICATIONS

Protection against contact heat up to 250°C for 15 seconds; precise welding, TIG welding; Plasma cutting, gouging, flame cutting work...

TECHNICAL FEATURES

Color	Grey	Finition back leather	Split leather
Shape	Glove	Type Of Cuff	Safety cuff / Straight cut
Gloves environment	High heat	Glove thickness - mm	0.7 - 0.9mm / 1.0 - 1.3mm
Glove type	Cut and sewn	Cuff length - mm	150
Support material	Premium full grain cowhide palm		
Support material 2	Split leather back		
Glove construction	Welding		
Palm material	Leather		
Type of palm leather	Cowhide		
Finition palm leather	Grain leather		
Back material	Leather		
Type of back leather	Cowhide		

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 2777/10432-02/E00-00

Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park- Clonee- Dublin 15 Dublin Ireland



EPI CAT. II

EN420:2003 + A1:2009

General requirements for protective gloves

EN388:2016



2.1.3.2.X.

Protection from mechanical risks

EN407:2004



4.2.2.X.4.X

Protection from heat and fire