

Ref. MO2480

### Thermal Protection

### Cold Insulation



COLD  
2

Thinsulate  
INSULATION

### The +

Optimized Dexterity  
Comfort  
Thinsulate liner :Reduced sweating  
Dirt resistant

### PURCHASE PACKAGING

Ref.	Size	Inner	Carton
2480	10	12	60

### SALES PACKAGING

>1

Multiple

See also

### VARIANTS



MO2475



MO2470

### DESCRIPTION

Yellow full grain superior cowhide leather  
Thinsulate beige full liner,  
Elastic band at the back of the wrist, with brown cotton bias

### SECTORS

- Maintenance
- Infrastructure, building industry
- Construction - finishing work
- Transport (excluding manufacturing) and logistics

### APPLICATIONS

Outdoor handling, winter transport,  
refrigerated handling and handling,  
mountain environment.

**TECHNICAL FEATURES**

<b>Color</b>	Beige	<b>Glove thickness - mm</b>	0.7 - 0.9mm
<b>Shape</b>	Glove		
<b>Gloves environment</b>	Intense cold		
<b>Glove type</b>	Cut and sewn		
<b>Support material</b>	Full grain cowhide		
<b>Glove construction</b>	Master		
<b>Palm material</b>	Leather		
<b>Type of palm leather</b>	Cowhide		
<b>Finition palm leather</b>	Grain leather		
<b>Back material</b>	Leather		
<b>Type of back leather</b>	Cowhide		
<b>Finition back leather</b>	Grain leather		
<b>Lining material</b>	Thinsulate fleece		
<b>Type Of Cuff</b>	Rolled edge / Elastic band at the back of the wrist		

**STANDARD(S)**

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate **2777/10222-02/E00-00**

Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park- Clonee- Dublin 15 Dublin Ireland



EPI CAT. II

**EN420:2003 + A1:2009**

General requirements for protective gloves

**EN388:2016**



2.1.2.2.X.

Protection from mechanical risks

**EN511:2006**



2.2.X

Protection from the cold

RETAILER STAMP