

Ref. MO23185

Non Reusable

FFP1 NR D



### The +

Specific design of the exhalation valve: high reduction of the breathing resistance  
 Optimal adherence of the mask: 3D flat fold and complet seal on upper part  
 Elastic band without latex

#### PURCHASE PACKAGING

Ref.	Size	Inner	Carton
23185	-		12

#### SALES PACKAGING

>1

Multiple

#### DESCRIPTION

FFP1 disposable foldable half mask in nonwoven polypropylene with electrostatic filter media and exhalation valve, latex free synthetic rubber, PU foam total nose seal,

#### APPLICATIONS

For occasional use in a very dusty environment. Protections against non-toxic solid and liquid aerosols, such as calcium carbonate, kaolin, cement, cellulose, sulfur, cotton, flour, coal, ferrous metals, vegetable oils and tender woods.  
 Textile industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork (strong woods excepted).

See also

#### VARIANTS



MO23180

## TECHNICAL FEATURES

<b>Shape</b>	3D mask	<b>Main risk</b>	Respiratory protection from aerosols and non toxic dust
<b>Weight</b>	15g	<b>Features</b>	Non woven SMS polypropylene with exhalation valve
<b>Specifications</b>	FFP1 NR D		Latex free synthetic rubber bands
<b>Harness features</b>	Synthetic elastic rubber (latex free)		Adjustable nose clip

## STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate 697918

Delivered by BSI Group The Netherlands B.V (2797) Say Building- John M. Keynesplein 9- 1066 EP Amsterdam Netherlands



EPI CAT. III

EN149:2001 + A1:2009  
FFP1 NR D

Particle filtering half masks