

Ref. MO23205

Non Reusable

FFP2 NR D



D

The +

Electrostatic filter media
Sliding elastic band: better adjustment
Latex free to prevent the risk of irritation
Exhalation valve: reduction of breathing resistance and avoid fog inside the mask

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
23205	-	-	12

SALES PACKAGING

>1

Multiple

DESCRIPTION

Foldable half-mask in nonwoven polypropylene with exhalation valve, latex free synthetic rubber, adjustable nose clip

SECTORS

- Heavy & process industries
- Chemical & pharmaceutical industries
- Light Industries
- Infrastructure, building industry
- Construction - finishing work
- DIY

APPLICATIONS

For occasional use in a very dusty environment. Protections against non-toxic solid and liquid aerosols, such as calcium carbonate, kaolin, cement, cellulose, sulfur, cotton, flour, coal, ferrous metals, vegetable oils and tender woods. Textile industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork (strong woods excepted).

TECHNICAL FEATURES

Shape	Flat foldable mask	Main risk	Respiratory protection from aerosols and low toxic dust
Weight	17g	Features	Foldable half-mask in non-woven polypropylen SMS with valve Latex free synthetic rubber Adjustable nose clip
Specifications	FFP2 NR D	Other features	welded outer contour ffp2 polypropylene sms
Harness features	Synthetic elastic rubber (latex free)		

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate 697918

Delivered by BSI Group The Netherlands B.V (2797) Say Building- John M. Keynesplein 9- 1066 EP Amsterdam Netherlands



EPI CAT. III

EN149:2001 + A1:2009
FFP2 NR D

Particle filtering half masks