

Ref. **MO23106**

Non Reusable

FFP1 NR D



The +

Electrostatic filter media
Elastic band without latex
Adjustable alu nose clip and comfortable nasal cushions with polyethylene foam

Exhalation valve: reduction of breathing resistance and avoid fog inside the mask

PURCHASE PACKAGING

| Ref. | Size | Inner | Carton |
|-------|------|-------|--------|
| 23106 | - | - | 12 |

SALES PACKAGING

>1

Multiple

DESCRIPTION

FFP1 disposable half mask in non-woven polypropylene with exhalation valve, latex free synthetic rubber

See also

SECTORS

- Farming, silviculture and fishing
- Mining
- Light Industries
- Maintenance
- Infrastructure, building industry
- Construction - finishing work
- DIY

APPLICATIONS

For occasional use in a very dusty environment. Protections against non-toxic solid and liquid aerosols, such as calcium carbonate, kaolin, cement, cellulose, sulfur, cotton, flour, coal, ferrous metals, vegetable oils and tender woods. Textile industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork (strong woods excepted).

VARIANTS



TECHNICAL FEATURES

| | | | |
|-------------------------|---------------------------------------|------------------|---|
| Shape | Hull mask | Main risk | Respiratory protection from aerosols and non toxic dust |
| Weight | 12g | Features | Nonwoven polypropylen with exhalation valve |
| Specifications | FFP1 NR D | | Latex free synthetic rubber headstrap |
| Harness features | Synthetic elastic rubber (latex free) | | Adjustable aluminum nose clip and PU foam nose pad |

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate CE 697918

Delivered by BSI Group The Netherlands B.V (2797) Say Building- John M. Keynesplein 9- 1066 EP Amsterdam Netherlands



EPI CAT. III

EN149:2001 + A1:2009
FFP1

Particle filtering half masks