

Ref. MO23216

Non Reusable

FFP2 NR D



D

The +

Specific design of the exhalation valve: high reduction of the breathing resistance
 Preformed design: fits with glasses or goggles to avoid the risk of condensation
 The ergonomic form offers an optimal adjustment to the face without nose clip.

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
23216	-		12

SALES PACKAGING

>1

Multiple

See also

VARIANTS



MO23211

DESCRIPTION

FFP2 half-mask made of non-woven polypropylene, external layer in polyester with exhalation valve, PU foam nose seal, latex free synthetic rubber

SECTORS

- Heavy & process industries
- Chemical & pharmaceutical industries
- Light Industries
- Infrastructure, building industry
- Construction - finishing work
- DIY

APPLICATIONS

For occasional use in a very dusty environment. Protections against non-toxic solid and liquid aerosols, such as calcium carbonate, kaolin, cement, cellulose, sulfur, cotton, flour, coal, ferrous metals, vegetable oils and tender woods. Textile industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork (strong woods excepted).

TECHNICAL FEATURES

Shape	Ergonomic mask	Main risk	Respiratory protection from aerosols and low toxic dust
Weight	15g	Features	FFP2 Polyester / polypropylène SMS
Specifications	FFP2 NR D		
Harness features	Synthetic elastic rubber (latex free)		

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate CE 697918

Delivered by BSI Group The Netherlands B.V (2797) Say Building- John M. Keynesplein 9- 1066 EP Amsterdam Netherlands



EPI CAT. III

EN149:2001 + A1:2009
FFP2 NR D

Particle filtering half masks