coverguard

TECHNICAL DATASHEET

EUROWELD 100

Ref.

1WEL10

Specialties





Welding





The +

Comfort, flexibility, dexterity, Elastic band on back of hand for better fitting,

Extended service life (para-aramide seams)

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
1WEL100008	8	10	60
1WEL100009	9	10	60
1WEL100010	10	10	60
1WEL100011	11	10	60

SALES PACKAGING

>1

Multiple

DESCRIPTION

Superior full grain goat leather, para-aramide stitch, wing thumb, elastic band on back of hand, safety cuff in orange split leather, length 15cm.

SECTORS

Mechanicals constructions

Energy (production and distribution)

Maintenance

Infrastructure, building industry

Transport (excluding manufacturing) and logistics

APPLICATIONS

Protection against contact heat up to 100°C for 15 seconds; Particularly recommended for precise welding, TIG welding; Plasma cutting, gouging, flame cutting work...

coverguard

TECHNICAL FEATURES

ColorGreyColor 2OrangeShapeGlove

Gloves environment Moderate heat Glove type Cut and sewn

Support material Superior full grain goat, cuff in

split cowhide

Glove construction Welding Seams material para-aramid

Type Of Cuff Safety cuff / Straight cut
Glove thickness - mm 0.7 - 0.8mm / 1.0 - 1.3mm

Cuff length - mm 150

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/162/04/21/0667

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France

 ϵ

EPI CAT. II

EN420:2003 + A1:2009

General requirements for protective gloves

EN388:2016 + A1:2018

A1.2018

Protection from mechanical risks

EN407:2004

Protection from heat and fire



EN12477:2001 + A1:2005 TYPE B

Protective gloves for welders