

Non Reusable

FFP2 NR D



The +

Preformed design: fits with glasses or goggles to avoid the risk of condensation
 The ergonomic form offers an optimal adjustment to the face, without nasal clip
 Exhalation valve: reduction of breathing resistance and avoid fog inside the mask

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
23276	-		12

SALES PACKAGING



Multiple

DESCRIPTION

FFP2 half-mask made of non-woven polypropylene with preformed shell and valve, external layer in polyester, PU foam nose seal, latex free synthetic rubber

SECTORS

- Heavy & process industries
- Chemical & pharmaceutical industries
- Light Industries
- Infrastructure, building industry
- Construction - finishing work
- DIY

APPLICATIONS

For occasional use in a very dusty environment. Protections against non-toxic solid and liquid aerosols, such as calcium carbonate, kaolin, cement, cellulose, sulfur, cotton, flour, coal, ferrous metals, vegetable oils and tender woods. Textile industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork (strong woods excepted).

TECHNICAL FEATURES

Shape	Ergonomic mask	Main risk	Respiratory protection from aerosols and low toxic dust
Weight	10g	Color	White
Specifications	FFP2 NR D	Color 2	Blue
Harness features	Synthetic elastic rubber (latex free)	Features	Polyester / polypropylene SMS

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate CE 697918

Delivered by BSI Group The Netherlands B.V (2797) Say Building- John M. Keynesplein 9- 1066 EP Amsterdam Netherlands



EPI CAT. III

EN149:2001 + A1:2009
FFP2 NR D

Particle filtering half masks