

Ref. MO2524

Specialties

Welding



The +

Comfort
Flexibility
Split leather back : better sparks protection

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
2524	10	12	60

SALES PACKAGING

>1

Multiple

DESCRIPTION

Full grain cowhide leather in palm, back in split cowhide leather,
Wing thumb
Safety cuff in split leather, length 15cm

SECTORS

- Mechanicals constructions
- Energy (production and distribution)
- Maintenance
- Infrastructure, building industry

APPLICATIONS

Protection against contact heat up to 250°C for 15 seconds; precise welding, TIG welding; Plasma cutting, gouging, flame cutting work...

TECHNICAL FEATURES

Color	Grey	Type of back leather	Cowhide
Shape	Glove	Finition back leather	Split leather
Gloves environme-nt	High heat	Type Of Cuff	Safety cuff / Straight cut
Glove type	Cut and sewn	Glove thickness - mm	0.7 - 0.9mm / 1.0 - 1.3mm
Support material	Premium full grain cowhide palm	Cuff length - mm	150
Support material 2	Split leather back		
Glove construct-ion	Welding		
Palm material	Leather		
Type of palm leather	Cowhide		
Finition palm leather	Grain leather		
Back material	Leather		

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 2777/25938-02/E00-00

Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park- Clonee- Dublin 15 Dublin Ireland



EPI CAT. II

EN ISO 21420:2020

Protective gloves – General requirements and test methods

EN388:2016
+ A1:2018

Protection from mechanical risks



2 . 1 . 3 . 2 X

EN407:2020

Protective gloves and other hand protective equipments against thermal risks (heat and/or fire)



4 . 1 . 2 . X . 4 X