

Ref. 1WEL14

Specialties

Welding



The +

From size 9 to 11
Comfort
Antistatic
Good value for money

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
1WEL140009	9	10	60
1WEL140010	10	10	60
1WEL140011	11	10	60

SALES PACKAGING



Multiple

DESCRIPTION

Split cowhide leather
Wing thumb
Safety cuff in split leather, length 15cm

SECTORS

- Energy (production and distribution)
- Maintenance
- Construction - finishing work
- Services and distribution

APPLICATIONS

Protection against contact heat up to 100°C for 15 seconds;
MMA welding (Rutile or cellulosic),
MAG/MIG welding (mixed gas or CO₂), coated wires; Plasma cutting, gouging, flame cutting work...

TECHNICAL FEATURES

Color	Grey	Glove thickness - mm	1.0 - 1.3mm
Shape	Glove	Cuff length - mm	150
Gloves environment	Moderate heat		
Glove type	Cut and sewn		
Glove construction	Welding		
Palm material	Leather		
Type of palm leather	Cowhide		
Finition palm leather	Split leather		
Back material	Leather		
Type of back leather	Cowhide		
Finition back leather	Split leather		
Type Of Cuff	Safety cuff / Straight cut		

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 2777/11676-03/E00-00

Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park- Clonee- Dublin 15 Dublin Ireland



EPI CAT. II

EN ISO 21420:2020

Protective gloves – General requirements and test methods

EN388:2016
+ A1:2018

Protection from mechanical risks



3.1.3.2.X.

EN407:2020

Protective gloves and other hand protective equipments against thermal risks (heat and/or fire)



4.1.2.X.4.X

EN12477:2001 + A1:2005
TYPE A

Protective gloves for welders

EN1149-2:1997

ESD safety gloves