

TECHNICAL DATASHEET

EUROSTRONG 260

MO260 Ref.

General & Heavy Duty Works





Textile/Leather



The +

Superior quality Safety cuff Vein protection patch Comfort Extended service life

PURCHASE PACKAGING

Ref. Size Inner Carton 260 10 10 100

SALES PACKAGING

>1

Multiple

DESCRIPTION

Docker glove in full grain cowhide, thickness, 1,2mm, Cotton lined palm, green canvas cuff and back, 8cm safety cuff

SECTORS

APPLICATIONS

Mining

Infrastructure, building industry

Construction - finishing work

Transport (excluding manufacturing) and logistics Heavy materials handling, wood and carpentry, masonry.

TECHNICAL FEATURES

ColorGreenColor 2EcruShapeGlove

Gloves environment Dry environment
Glove type Cut and sewn
Support material Full grain cowhid

Full grain cowhide and cotton

canvas

Glove construction Docker
Palm material Leather
Type of palm leather Cowhide
Finition palm leather Grain leather

Back material Cotton

Back material type Reinforced part place Reinforced part material Lining material Type Of Cuff

Glove thickness - mm

Cotton canvas

Back

Leather/Split leather

Cotton

Safety cuff / Artery protector /

Straight cut

0.7 - 0.9mm

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 2777/12314-01/E00-00

Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park- Clonee- Dublin 15 Dublin Ireland

Protection from mechanical risks

 ϵ

EPI CAT. II

EN420:2003 + A1:2009

General requirements for protective gloves

EN388:2016