

Thermal Protection

Heat Resistance



The +

Long cuff for better protection ;
High combined protection against heat and cuts ;
Thermal insulation up to 500°C / 15 sec.

PURCHASE PACKAGING

| Réf. | Taille | Sachet | Carton |
|------|------------|--------|--------|
| 4657 | 10 - 35 cm | 5 | 50 |

SALES PACKAGING

>1

Multiple

DESCRIPTION

Tough seamless support from Kevlar® ; heavyweight Cotton lining ; 15cm long cuff, total length 33cm.

SECTORS

- Heavy & process industries
- Mechanicals constructions
- Light Industries
- Maintenance

APPLICATIONS

General and heavy handling of sharp and hot objects (aluminium/metal profiles), handling in metallurgy and steel industry.

TECHNICAL FEATURES



Gauge 5

| | |
|----------------------------|-----------------------------------|
| Color | Yellow |
| Shape | Glove |
| Environment | Extreme heat |
| Glove type | Seamless knitting |
| Support material | Kevlar® brand heavy seamless knit |
| Support material 2 | Thick cotton |
| Material of coating | Without |
| Type Of Cuff | Straight cut / Elastic wrist |
| Length - mm | 330 |

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate **2777/12298-01/E00-00**

Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park- Clonee- Dublin 15 Dublin Ireland



EN420:2003 + A1:2009

EN388:2016



1.X.4.0.D.

EN407:2004



4.4.X.X.X.X

EPI CAT. II

General requirements for protective gloves

Protection from mechanical risks

Protection from heat and fire

RETAILER STAMP