

Ref. MO4700

Thermal Protection

Heat Resistance



HOT
2

The +

Thermal contact insulation 250°C / 15 sec.
Comfortable terry cotton

PURCHASE PACKAGING

Réf.	Taille	Sachet	Carton
4700	10	5	60

SALES PACKAGING

>1

Multiple

DESCRIPTION

100% terry cotton support 815 g/m² ; with elasticated wrist.

SECTORS

- Heavy & process industries
- Mechanicals constructions
- Light Industries
- Maintenance

APPLICATIONS

General and heavy handling of hot objects: exiting furnaces, injection moulding machines, glass industry, metal working.

TECHNICAL FEATURES

Color	Ecu
Shape	Glove
Environment	High heat
Glove type	Cut and sewn
Support material	Cotton terry liner
Glove construction	Master
Palm material	Cotton
Palm material type	Cotton terry liner
Back material	Cotton
Back material type	Cotton terry liner
Type Of Cuff	Elastic wrist

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate **8064 Issue 1**

Delivered by SATRA Technology Centre Ltd (0321) Wyndham Way Telford Way Kettering- Northamptonshire- NN16 8SD United Kingdom



EN420:2003 + A1:2009

EN388:2016



2.2.3.1.X.

EN407:2004



X.2.X.X.X.X

EPI CAT. II

General requirements for protective gloves

Protection from mechanical risks

Protection from heat and fire

RETAILER STAMP