

Specialties

High

High shoes



The +

- *Welding sparks protective cover.
- *Front protection
- *Footbridge supplying torsional rigidity.
- *Defined heel for better safety especially on ladders.

PURCHASE PACKAGING

Ref.	Size	Carton
9BASA10038	38	6
9BASA10039	39	6
9BASA10040	40	6
9BASA10041	41	6
9BASA10042	42	6
9BASA10043	43	6
9BASA10044	44	6
9BASA10045	45	6
9BASA10046	46	6
9BASA10047	47	6

Some sizes may only be available in certain countries

DESCRIPTION

The BASALT model is a shoe that perfectly meets the requirements of the welding, foundry or metallurgy professions. It is both comfortable and practical thanks to its breathable mesh lining and its Velcro fastening system for quick removal of the shoes. Its fireproof Kevlar seams and its sole resistant to very high temperatures (up to 300°C for one minute) make it ideal for work in extremely high temperature environments.

TECHNICAL FEATURES

Color	Black	Main assembly	Injected
Weight	675 g	Closing	Scratch closure
Upper	Full grain leather	Lining	Breathable 3D mesh
Toecap	Steel	Defined heel	
Puncture resistant sole	Steel		
Midsole	PU		
Outsole	Rubber nitrile		
Insole	Removable, textile and foam		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/03/22/0528

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe $0,1M \Omega < A < 1000 M \Omega$ + Fuel and oil resistant contact outsole + Energy absorbing heel $E \geq 20$ Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

HI

Sole insulation against heat (30 minutes at 150°C)

HRO

Heat contact resistant outsole (60 seconds at 300°C)

WG

Resistance of leather to molten metal splash

EN ISO 20349-2:2017 + A1:2020

Footwear for risk protection in foundries