

Specialties

High

High shoes



The +

- *Welding sparks protective cover.
- *Front protection
- *Footbridge supplying torsional rigidity.
- *Defined heel for better safety especially on ladders.

PURCHASE PACKAGING

Ref.	Size	Carton
9QAND10038	38	6
9QAND10039	39	6
9QAND10040	40	6
9QAND10041	41	6
9QAND10042	42	6
9QAND10043	43	6
9QAND10044	44	6
9QAND10045	45	6
9QAND10046	46	6
9QAND10047	47	6

Some sizes may only be available in certain countries

DESCRIPTION

The QANDILITE II is a full grain leather "welder's" shoe with a padded malleolus guard for better protection.

It is both comfortable and practical thanks to its breathable mesh lining and its Velcro fastening system for quick removal.

This metal-free safety shoe has a composite toe cap and a textile anti-perforation sole for added flexibility and lightness. Its Kevlar fireproof seams and its sole resistant to very high temperatures (up to 300°C for one minute) make it ideal for work in extremely high temperature environments.

TECHNICAL FEATURES

Color	Black	Main assembly	Injected
Weight	713 g	Closing	Scratch closure
Upper	Full grain leather	Lining	Breathable 3D mesh
Toecap	Composite	Defined heel	
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	Rubber nitrile		
Insole	Removable, textile and foam		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate ITASLNB21008827

Delivered by INTERTEK Italia S.p.A. (2575) Via Guido Miglioli 2/A 20063 Cernusco sul Naviglio - Milano (MI) Italy



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe $0,1M \Omega < A < 1000 M \Omega$ + Fuel and oil resistant contact outsole + Energy absorbing heel $E \geq 20$ Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

HI

Sole insulation against heat (30 minutes at 150°C)

HRO

Heat contact resistant outsole (60 seconds at 300°C)