coverguard

TECHNICAL DATASHEET

FREELUX

K

Ref. MO62139

Safety Glasses



The +

Polarized lenses: accentuated contrasts and reliefs Flexible and self-adjustable temple Anti-slip tip Anti-slip nose bridge

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
62139	-	10	120

SALES PACKAGING



Hangable individual polybag

See also



DESCRIPTION

FREELUX safety glasses. Polycarbonate polarized lens, anti-scratch K treatment, nylon frame, auto-adjustable co-material temples with soft PVC tips, side protection with venting holes, not compatible with car driving

SECTORS

Farming, silviculture and fishing

Light Industries

Infrastructure, building industry

Transport (excluding manufacturing) and logistics

coverguard

FREELUX

TECHNICAL FEATURES

Shape	Safety Glasses
Weight	25g
Lens	Polycarbonate 2.3mm
Lens marking	5-3.11F
Frame	Nylon
Frame marking	F - CAT 3
Temple material	Nylon + PVC

TemplesNot adjustableShadePolarizedMain riskEye protectionColorBlackFeaturesAnti-scratch K treatment
Polarized lensesOther featuresSport style design

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate PPE22162363

Delivered by INSPEC International B.V. (2849) Beechavenue 54-1119 PW Schiphol-Rijk Netherlands

CE	EPI CAT. II
EN166:2001	Specifications (optical quality, resistance to usual risks, mechanical risks, resistance to impacts)
EN 172:1994 + A1 :2000 + A2:2001	Sunglare filters for industrial use

RETAILER STAMP

MAJ 24/03/2023