

Ref. MO62127

Safety Glasses



The +

- Flexible and self-adjustable temple
- Anti-slip tip
- Anti-slip nose bridge

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
62127	-	10	120

SALES PACKAGING



Hangable individual polybag

See also

VARIANTS



DESCRIPTION

FREELUX safety glasses. Polycarbonate in/out lens, anti-UV 400 treatment, nylon frame, auto-adjustable co-material temples with soft PVC tips, side protection with venting holes

SECTORS

- Mechanicals constructions
- Light Industries
- Maintenance
- Infrastructure, building industry
- Construction - finishing work
- DIY
- Transport (excluding manufacturing) and logistics

TECHNICAL FEATURES

Shape	Safety Glasses	Temples	Not adjustable
Weight	25g	Shade	In/Out
Lens	Polycarbonate 2.3 mm	Main risk	Eye protection
Lens marking	5-1.7 1F	Color	Black
Frame	Nylon	Color 2	Grey
Frame marking	F - CAT 1	Features	Anti-UV 400 treatment
Temple material	Nylon + PVC	Other features	Sport style design

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate PPE22162363

Delivered by INSPEC International B.V. (2849) Beechavenue 54- 1119 PW Schiphol-Rijk Netherlands



EPI CAT. II

EN166:2001

Specifications (optical quality, resistance to usual risks, mechanical risks, resistance to impacts)

EN 172:1994 + A1 :2000 + A2:2001

Sunglare filters for industrial use

ISO 12312-1:2013

Sunglare filters for leisure and sport

RETAILER STAMP