

Ref. **9XCWH70**

Outdoor

High

High shoes



The +

PERFORMANCE : waterproof membrane (marked S7S) to keep feet dry // high cleats designed to promote grip and stability

COMFORT : insert for good cushioning and joint vibration prevention

DURABILITY : carbon toe cap for greater lightness and thermal insulation // rigid laces and riveted eyelets for greater durability

DESCRIPTION

X-CLAW PROOF is a waterproof, full-grain fat leather safety shoe. Its reinforcements at the front (SC marking) and back of the foot provide protection and durability. X-CLAW PROOF has been designed for use in damp environments.

Its membrane keeps feet dry after a day's work.

X-CLAW is above all a unique sole designed to offer grip, stability and durability:

- Its large, inverted studs provide grip on all loose and uneven surfaces.
- Its rear platform and transverse studs (LG marking) ensure safety and prevent the risk of falling, even on ladders.
- Its wear indicator and the quality of its PU also contribute to its durability.

As for the upper, its carbon toe cap provides impact resistance, lightness, thinness and does not conduct heat.

The ankle insert (AN marking) provides extra protection.

Riveted eyelets and a rigid lace ensure easy lacing, good all-day support and durability.

The soft, padded strap, high rise gusset and podiatrist-approved insole all contribute to the shoe's comfort.

X-CLAW PROOF has been tested and approved by professional.

PURCHASE PACKAGING

Ref.	Size	Carton
9XCWH70035	35	6
9XCWH70036	36	6
9XCWH70037	37	6
9XCWH70038	38	6
9XCWH70039	39	6
9XCWH70040	40	6
9XCWH70041	41	6
9XCWH70042	42	6
9XCWH70043	43	4
9XCWH70044	44	4
9XCWH70045	45	4
9XCWH70046	46	4
9XCWH70047	47	4
9XCWH70048	48	4

Some sizes may only be available in certain countries

See also

SECTORS

APPLICATIONS

TECHNICAL FEATURES

Color	Brown	Insole	Removable, textile and foam
Color 2	Black	Main assembly	Injected
Weight	768 g	Front bumper	
Upper	Full grain leather	Reinforcement material	TPU
Toecap	Carbon	Closing	Lacing closure
Puncture resistant sole	Textile	Lining	Breathable 3D mesh / Insulation membrane
Midsole	PU	Defined heel	
Outsole	PU		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 5 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **CE-PC-240530-249-01-9B**

Delivered by CCQS Certification Services Limited (2834) Block 1 Blanchardstown Corporate Park- Ballycoolin Road- Blanchardstown- Dublin 15 D15 AKK1 Dublin Ireland



EPI CAT. II

WR

Water repellent shoe

HI

Sole insulation against heat (30 minutes at 150°C)

CI

Shoe insulation against cold (30 minutes at -20°C)

ESD

Electrostatic discharge shoe (EN 61340-5-1 standard)

COVERPERF - Damping



Shoes tested in a certified laboratory (CTC) offering excellent damping. Over 25% of the impact force is absorbed by the sole.

EN ISO 20345:2022

EN ISO 20345:2022
S7S

Safety shoes

S7S Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton and:- closed heel area- antistatic properties- energy-absorbing capacity of the heel Puncture resistance: - Sole puncture resistance (1100 Newton) - Non-metallic insert, 3.0mm diameter puncture needle-resistance to penetration and water absorption of the upper- puncture resistance according to type- cleated outsole - non-metallic insert type PS+ Water resistance of the entire shoe

SR

Resistance to slippage (ceramic floor + oil)

MAJ 21/02/2026 LG

Grip System - Unhooked heel