coverguard®

Technical datasheet

ASTER

MO71343 Ref.

Rope Grabs



DESCRIPTION

Coated spliced ends and Material Caract.

loops with thimbles

Weight 2,6 kg 10 years

Service life

Rope grab in zync plated

steel.

Twisted polyamide rope Ø 14 mm in 10 m length Coated spliced ends and

loops with thimbles.

Length 10 m

Connector Steel screw karabiner on

the rope grab

Capacity User of 100 kg

Breaking > 15 kN

strength

Detachable







The +

- * Automatic function for vertical use
- * With manual locking option for work on sloped roofs or in restraint

PURCHASE PACKAGING

Ref. Carton

71343 5

SALES PACKAGING



Individual polybag

APPLICATIONS

- * Guided type fall arrest system for vertical, horizontal use or sloped surfaces
- * Connecting element for a fall arrest or restraint system

See also

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate 2777/10357-03/E05-01 Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park-Clonee- Dublin 15 Dublin Ireland



PPE Cat. III

EN353-2:2002

Guided type fall arresters including a flexible anchor line

VARIANTS





MO71343M

MO71344