

Ref. MO8910

Specialties



Classe	Tension max. d'utilisation COURANT ALTERNATIF
00	500 V
0	1 000 V
1	7 500 V
2	17 000 V
3	26 500 V
4	36 000 V



Catégorie	Résistant à
A	Acide
H	Huile
Z	Ozone
R	Acide, Huile, Ozone
C	Très basse température
Protection mécanique	

Electric Related



SUR
COMMANDE
ON
DEMAND

MADE IN
FRANCE

The +

CLASS 4 - RC

Integrated mechanical protection (no leather protector required)

2 in 1 insulation: dielectric and mechanical protection

Supplied with a pair of cotton mittens to improve comfort (recommended to replace them regularly for hygienic reasons)

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
8908	8		50
8909	9		50
8910	10		50
8911	11		50

SALES PACKAGING



Individual polybag

DESCRIPTION

Composite gloves: natural rubber with outer coating in orange red elastomer, black interior, cut edges.

Special properties (category) RC, with mechanical protection.

Gloves with reinforced mechanical protection: no need any leather over gloves.

Product made with a high-performance polymer blend that combines mechanical, chemical and dielectric resistances.

Fingerless cotton under-gloves can be used in conjunction in order to absorb the sweat and ensure greater hygiene, while preserving dexterity.

Length : 41 cm

SECTORS

Manufacture of electrical and electronic equipment and machines

Energy (production and distribution)

Maintenance

APPLICATIONS

Electrical work, live working
Max operating voltage : 36000v
Proof test voltage : 40000v

TECHNICAL FEATURES

Color	Red
Shape	Glove
Gloves environment	Dry environment
Glove type	Dipping
Tempered glove structure	Non supported
Support finition	Smooth
Type Of Cuff	Straight cut
Length - mm	410

STANDARD(S)



EN420:2003 + A1:2009

EPI CAT. III

General requirements for protective gloves

EN60903:2003 + CEI 60903:2014

Electrical insulating gloves



CLASS 4