coverguard®

TECHNICAL DATASHEET

WELDING BLANKET 550°C

weltek

Ref. 2TOI550

Welding accessories

Collective protection



MADE IN FRANCE

The +

*Low amperage welding
*Grinding
*Vertical use
*Partitions

AVAILABLE VERSIONS

Ref.	Version
CH0551	1000x1000mm
CH0552	2000x1000mm
CH0553	2000x2000mm
CH0554	3000x2000mm
CH0555	3000x3000mm
CH0556	4000x3000mm
CH0557	4000x4000mm
CH0558	25x1m
CH0559	Special Dimensions

DESCRIPTION

The 550°C protective blanket is made of fiberglass and offers a peak resistance of 550°C. The fire resistance classification of the 550°C fabric is M0, the highest. Can be used vertically, and horizontally for low welding/grinding spatters. With a thickness of 1mm and a weight of 635g/m², the 550°C protective canvas remains light, manageable and resistant. The 550°C protective blanket is available in sizes 1x1m, 2x1m, 2x2m, 3x2m, 3x3m, 4x3m, 4x4m as well as in rolls of 25x1m or 25x12m. Custom made and eyelet installation is also possible.

COVERGUARD
120 rue Michel Girer, 01390 Mionnay FRANCE - Tél +33 4 72 26 57 57

TECHNICAL FEATURES

Features	Fiberglass Hemmed edges
Weight	635g/m²
Thickness	1,00mm
Peak resistance	550°C
Fire resistance	M0
Standard resistance	450°C

STANDARD(S)

EN13501-1:2018

A1

Fire classification of construction products and building elements

SPARE PARTS

MAJ 20/04/2026

COVERGUARD
120 rue Michel Girer, 01390 Mionnay FRANCE - Tél +33 4 72 26 57 57