

Ref. 1CRAN

Cut - Precision Work

Oily Environment



The +

COVERPERF DURABILITY: Ultra high abrasion resistance
Oil and grease-proof (reduces the risk of dermatitis)
Excellent grip in oil
Ergonomical shape: reduces muscle fatigue and improves productivity

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
1CRAN06	6	5	50
1CRAN07	7	5	50
1CRAN08	8	5	50
1CRAN09	9	5	50
1CRAN10	10	5	50
1CRAN11	11	5	50

DESCRIPTION

Mottled grey seamless support from HPPE, mineral fibre, polyamide, elastane,
Double coating 3/4 hand in smooth blue nitrile and black nitrile sandy finish for the palm,
Ergonomic shape,
Knitted wrist

SALES PACKAGING

Hangable individual polybag

See also

VARIANTS

SECTORS

Heavy & process industries

Light Industries

Maintenance

Services and distribution

APPLICATIONS

Machining of parts in the presence of cutting oil, handling of sheets, handling of oiled mechanical parts, handling and sorting of small cutting parts, handling of glass plates, other industries, maintenance work in an oily environment (water, oils, greases, hydrocarbons), cutting, stamping.



1CRFN

TECHNICAL FEATURES



Gauge 13

Color	Grey	Coating finition 2	Sandy
Color 2	Blue	Type Of Cuff	Elastic wrist
Color 3	Black		
Shape	Glove		
Gloves environment	Oily		
Glove type	Seamless knitting		
Support material	HPPE polyamide elastane		
Coating level	3/4		
Material of coating	Nitrile		
Coating finition	Smooth		
Coating level	Palm		
Material of coating	Nitrile		

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/162/03/23/0358

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN388:2016
+ A1:2018



4.X.4.3.D.

Protection from mechanical risks

EN ISO 21420:2020
EN ISO 21420:2020

Protective gloves – General requirements and test methods

EN407:2020



X.1.X.X.X.X

Protective gloves and other hand protective equipments against thermal risks (heat and/or fire)

COVERPERF -
Durability/Abrasion resistance

COVERPERF - Durability/Abrasion resistance

