coverguard®

TECHNICAL DATASHEET

EUROCUT SLEEVE 450

Ref.

1CSLE004

Cut - Precision Work







Dry Environment







The +

Extra thin knitted part on the hand with anatomical shape and thumb hole.
Specifically developed to be worn with a glove.

Heat protection 100°C / 15 sec. Available in 2 length 45 / 60cm 1 piece.

PURCHASE PACKAGING

 Ref.
 Size
 Inner
 Carton

 1CSLE00450
 45cm
 12
 120

SALES PACKAGING

Hangable individual polybag

See also

DESCRIPTION

Grey seamless supported sleeve from HDPA, polyester, elastane, 13 gauge, hook and loop arm adjustment, extra-thin knitted part on the hand with anatomical shape and thumb hole, ambidextrous.

Length: 450mm

1 piece

SECTORS

Heavy & process industries

Light Industries

Transport (excluding manufacturing) and logistics

Services and distribution

APPLICATIONS

General handling with heat and cut protection needed.

Automotive Manufacturing, metal fabrication, sheet metal fabrication, metal stamping, canning, recycling, assembly, glass handing, pulp and paper processing ...

VARIANTS



1CSLE006

TECHNICAL FEATURES

Gauge 13

Color Grey Color 2 Black Shape Cuff

Dry environment Gloves environment Glove type Seamless knitting

Support material HDPA polyester elastane

Material of coating Without Seams material para-aramid

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/162/08/22/1573

Protection from mechanical risks

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France

CE

EPI CAT. II

EN ISO 21420:2020

Protective gloves – General requirements and test methods

EN388:2016

+ A1:2018



EN407:2020

X.1.X.X.X.X

Protective gloves and other hand protective equipments against thermal risks (heat and/or fire)

MAJ 13/03/2025