

Ref. 1CUNC00

Cut - Precision Work



Dry Environment



The +

RESISTANT : Crotch between thumb and index
Dexterity
Good grip in slightly oily areas

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
1CUNC00007	7	5	50
1CUNC00008	8	5	50
1CUNC00009	9	5	50
1CUNC00010	10	5	50
1CUNC00011	11	5	50
1CUNC00012	12	5	50

SALES PACKAGING

Hangable individual polybag

See also

VARIANTS



1CUCC00

DESCRIPTION

Blue seamless support from HDPE, polyester, elastane, 13 gauge,
Black nitrile foam palm coating,
Nitrile patch reinforcement between thumb and index
Knitted wrist.

SECTORS

- Heavy & process industries
- Light Industries
- Infrastructure, building industry
- Transport (excluding manufacturing) and logistics

APPLICATIONS

Handling in dry or slightly oily environments, assembly of parts, mechanical engineering, automotive, glass, construction and building industries, communities and public services, maintenance, woodworking, etc.

TECHNICAL FEATURES



Gauge 13

Color	Blue
Color 2	Black
Shape	Glove
Gloves environme-nt	Dry, slightly oily environment
Glove type	Seamless knitting
Support material	HDPE polyester elastane
Coating level	Palm
Material of coating	Nitrile
Coating finition	Foam
Reinforce-d part place	Between thumb and index finger
Reinforce-d part material	Nitrile
Type Of Cuff	Elastic wrist

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/162/07/20/1926

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN420:2003 + A1:2009

General requirements for protective gloves

EN388:2016



Protection from mechanical risks

4 . X . 4 . 3 C

ANSI

Cut resistance ANSI/SEA 105-2016 / ASTM F2992M-15

