coverguard®

TECHNICAL DATASHEET

EUROCUT N300

Ref. 1C

1CUNC00

Cut - Precision Work









Dry Environment







The +

RESISTANT : Crotch between thumb and index

Dexterity

Good grip in slightly oily areas

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
1CUNC00007	7	5	50
1CUNC00008	8	5	50
1CUNC00009	9	5	50
1CUNC00010	10	5	50
1CUNC00011	11	5	50
1CUNC00012	12	5	50

SALES PACKAGING

Hangable individual polybag

See also

VARIANTS



1CUCC00

DESCRIPTION

Blue seamless support from HDPE, polyester, elastane, 13 gauge, Black nitrile foam palm coating,

Nitrile patch reinforcement between thumb and index Knitted wrist.

SECTORS

Heavy & process industries

Light Industries

Infrastructure, building industry

Transport (excluding manufacturing) and logistics

APPLICATIONS

Handling in dry or slightly oily environments, assembly of parts, mechanical engineering, automotive, glass, construction and building industries, communities and public services, maintenance, woodworking, etc.

TECHNICAL FEATURES

Gauge 13

Color Blue Color 2 Black Shape Glove

Dry, slightly oily environment Gloves environment

Glove type Seamless knitting

HDPE polyester elastane Support material

Coating level Palm Material of coating Nitrile Coating finition Foam

Reinforced part place Between thumb and index

finger

Reinforced part material Nitrile Type Of Cuff Flastic wrist

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/162/03/25/0712

Protection from mechanical risks

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France

CE

EPI CAT. II

EN ISO 21420:2020

Protective gloves – General requirements and test methods

EN388:2016

+ A1:2018



4.X.4.3.C.

ANSI

Cut resistance ANSI/SEA 105-2016 / ASTM F2992M-15

